

**28230050****EXTRA MATT****ultra-matt washable waterborne paint**

An ultra-matt washable waterborne paint. Its excellent qualities, coverage and whiteness make it ideal for obtaining an excellent uniform effect on the wall and for concealing defects. EXTRA MATT is easy to apply with a roller and brush also on ceilings and tall walls, thanks to its non-drip properties. EXTRA MATT is formulated with a low VOC content for ecological reasons, to respect the environment.



<b>Date of revision</b>	03/11/2021
<b>Composition</b>	Single-component, physically drying matt vinyl paint in aqueous dispersion for the finishing coat. Classification as per UNI 8681: B4.C.0.A.2.HA
<b>Main properties</b>	<ul style="list-style-type: none"> <li>• ultra-matt</li> <li>• excellent whiteness</li> <li>• non-drip</li> <li>• excellent results also on plasterboard</li> <li>• washable</li> </ul>
<b>Applications</b>	Used in building works as a breathable, water-repellent waterborne paint with low VOC content, formulated with selected vinyl resins. A refined finish, it prevents condensate build-up thanks to its water-repellent properties. It does not contain significant amounts of formaldehyde, to the benefit of a healthy living environment.
<b>Colour</b>	Bianco Base.

Technical specifications (data measured at 20°C, with 65% R.H.)	Reference	UoM	Value
Water-vapour permeability	UNI EN ISO 7783		Class V1 high permeability
Gloss	EN ISO 13300	GU	3.5 @ 85°
Grain structure	EN ISO 13300	µm	<100 fine
Resistance to brushing while wet	EN ISO 13300		Class 3

**Method of use**

. Surface and application conditions	Ambient temperature min +5°C / max +35°C R.H. < 80%. Surface temperature min +5°C / max +35°C R.H. < 10%.
. Application method	Brush, roller, airless.
. Thinner	Water.
. Dilution	Roller 20–30%, brush 20–40%, airless 25–40%.

Rival is a trademark of  
Colorificio Sammarinese S.p.A.  
Via del Camerario 7  
47891 Falciano, San Marino  
T +378 (0549) 905 515  
F +378 (0549) 908 453  
colorificio@colsam.com  
colsam.com

C.o.e. SM00026  
Fully paid-up share capital € 3,000,000.00  
Legal title  
no. 26 dated 20 May 1944



- . Mixing Mix the product with care, adding water gradually until you reach the correct viscosity.
- . Theoretical coverage 14–16 m<sup>2</sup>/l per coat, depending on the absorbency of the support.

---

**Application cycle****NEW SURFACES**

The wall must be well seasoned, dry and dust free, without impurities of any kind, including loose sand or grit. Nonetheless, one coat of FA01 Fissacril Forte waterborne sealer fixative or FA12 RIVALFIX solvent-based sealer fixative enhances adhesion, eliminates chalking, uniforms the support's absorbency, reduces the risk of marks forming and reduces consumption of waterborne paint.

**PAINTED SURFACES**

Remove old peeling paint with a scraper or brush or apply a paint stripper if the paint does not come away easily in all points. Tempera paint must also be removed by washing the surface. The first coat of EXTRA MATT must be applied more diluted compared to the successive coats, to favour its penetration into the support.

---

**Notes**

Any hardened drops can be easily removed with Diluente Nitro 92100012 thinner.

**Storage**

Do not allow to freeze; store between +5°C and +20°C. Once opened, the undiluted product can be kept for 3 months in the closed container stored in the dark.

**Warnings**

Wash brushes and tools immediately after use; do not dump the wash water on the ground or into groundwater.

Keep out of reach of children.

For further information, consult the safety data sheet.

---

**VOC Classification - Directive 2004/42/EC - Italian Legislative Decree no. 161/2006**

A/A -, maximum 30 g/l (2010).

Maximum VOC content of EXTRA MATT ready for use: 30 g/l.

---

**Specification items**

Apply 2 coats of EXTRA MATT extremely matt washable waterborne paint in the colour desired by the work supervisor, after suitably preparing the surfaces to be treated. Includes materials and application, excludes skimming and/or scaffolding.

---

This information is the result of our practical experience but is purely indicative. For more detailed information, please contact our technical support service. This sheet cancels and substitutes any previous editions.

---