



Colorificio
Sammarinese
SpA

Via del Camerario 7
47891 Falciano, San Marino

T +378 (0549) 905 515
F +378 (0549) 908 453

colorificio@colsam.com
colsam.com

c.o.e SM00026
Fully paid-up share capital
€ 3.000.000,00
Legal title
no. 26 dated 20 May 1944

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
ISO 9001

74200401

SAM.O.VER TRASPARENTE INCOLORE elegant waxed finish



A water-repellent satin varnish ideal for use as a primer and finish. Formulated for coating door and window frames, blinds, shutters, doors, wooden gates. Protect surfaces against weathering and does not peel.



Date of revision

03 March 2017

Composition

A simple, single-component, semi-glossy alkyd finishing paint in solution with chemical oxidative drying for surface impregnation.
Classified according to UNI 8681: B0.A.0.B.1.AB.

Main properties

- stylish visual impact
- high outdoor resistance
- water-repellent

Applications

A coloured primer and finishing impregnating product with wax effect for exteriors and interiors. Ideal for preserving and decorating wood and for making it water-repellent. Contains a special additive (UV filter) that protects wood against ultraviolet rays and weathering, without altering its open-pore appearance. Creates a velvety and stylish finish that does not deteriorate over time due to peeling.

Formulated for the final coating of door and window frames, blinds, shutters, doors, matchboards, entrance doors, wooden gates.

Colour

Transparent base, swatch shades.

It can be coloured with the Colormaker tinting system; the number of available bases is indicated in the catalogue and in the Colormaker Lab software.

Technical characteristics	Reference	UoM	Value
(data measured at 20°C, with 65% R.H.)			
Specific weight (pycnometer)	C022	kg/l	0.850 ± 0.030
Viscosity Ford cup no. 4	C042	sec	14 ± 1
Dry residue	C033	%	39.0 ± 2.0
Dust-free drying		min.	90
Tack-free drying		hours	12-24
Dry-hard drying		hours	24
Coat-over time		hours	24



**Colorificio
Sammarinese
SpA**

Via del Camerario 7
47891 Falciano, San Marino

T +378 (0549) 905 515
F +378 (0549) 908 453

colorificio@colsam.com
colsam.com

c.o.e SM00026
Fully paid-up share capital
€ 3.000.000,00
Legal title
no. 26 dated 20 May 1944

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
ISO 9001

Method of use

. Surface and application conditions	Ambient temperature min. +5°C / max. +35°C and R.H. < 60%. Temperature of the support min. +5°C / max. +35°C and at least 3°C above the dew point.
. Application method	Brush, spraying, immersion, cloth.
. Thinner	9110.0001.
. Dilution	Ready for use.
. Theoretical coverage	14-16 m ² /l depending on the surface's absorption.

Application cycle

ON NEW WOOD

Sand using fine-grit sandpaper in the direction of the grain.
Apply a first coat of SAM.O.VER undiluted, using a brush, in the chosen wood shade and even out the product in the direction of the grain. After 12-24 hours, sand the surface lightly and apply the second coat.

ON WOOD PAINTED WITH FLATTING OR OPAQUE VARNISHES

Strip the old paints completely until the wood is exposed, using the appropriate methods.

Proceed as you would for new wood.

Notes

The support must be dry and well clean.

All subsequent coats after the first coat must nonetheless be applied when the previous coat is dry hard.

Longer drying times may be required in certain application conditions without this undermining the quality of the product. When applied outdoors, verify that the surface is perfectly dry and, if not, wait until it dries.

Take care to mix the product thoroughly before application to even out possible deposits.

Different production batches of the product, in the wood shades, could have slight shade variations: verify before starting the product's application.

Storage

In tightly closed containers, in a cool and dry place, protected against frost and heat sources.

Warnings

Work in well-ventilated environments and wear suitable personal protective equipment. Wash the brushes and tools immediately after use with thinner, and do not disperse the containers in the environment.

Keep out of reach of children.

For further information, consult the safety data sheet.

VOC classification - Directive 2004/42/EC - Italian Legislative Decree 161/2006

F/S -, maximum 700 g/l (2010).

Maximum VOC content of SAM.O.VER TRASPARENTE INCOLORE ready for use: 579,200 g/l.

Specification items

Apply 2 coats of 74200401 SAM.O.VER TRASPARENTE INCOLORE, an elegant waxed finish, in the colour desired by the work supervisor, after suitably preparing the surfaces to be treated. Includes materials and application, excludes skimming and/or scaffolding.

This information is the result of our practical experience but is purely indicative. For more detailed information, please contact our technical support service. This sheet annuls and replaces any previous editions.
